



## XML-file parameters reference guide

Last update 03/03/2022

# Table of contents

- 1 Intellect base ..... 4
- 2 Intellect Web Report System ..... 5
- 3 FACE-Intellect ..... 9
- 4 Axxon Player ..... 10

## Contents

- [Intellect base](#)
- [Intellect Web Report System](#)
- [FACE-Intellect](#)
- [Axxon Player](#)

# 1 Intellect base

XML file	Parameter	Available values	Default	Product version	Parameter in effect
<Archive storage drive>: \\VIDEO\Settings.xml	RotateAngle	0, 90, 180, 270	0		<p>Sets the rotation angle of video image in the archive. If the rotation angle is specified in the video camera settings (see <a href="#">Configuring a rotation angle of video image</a>), then this parameter is set automatically in Settings.xml file.</p> <p>In <i>Axxon player</i> the archive is rotated at the specified angle when being played back or exported.</p>
	SyncedTime	Date and time in the following format: DD-MM-YY hh:mm:ss	-		<p>Shows time of last import from edge storage as DD-MM-YY hh:mm:ss</p> <p>The import is performed from the time specified in the parameter if the number of hours does not exceed the time set by IpStorageSyncDepthHours registry key (see <a href="#">Registry keys reference guide</a>)</p> <p>The parameter can be changed by UPDATE_TIME command (see <a href="#">IPSTORAGE</a>).</p>
C: \\ProgramData\\elasticsearch-2.0.1\\config\\elasticsearch.yml	http.port	0 - 65536	9200	up to Intellect 4.10.2	The parameter sets the port occupied by Elastic Search search engine. The value is to be the same as one specified in the cam_title.run.config file (see below).
C: \\ProgramData\\elasticsearch-5.2.2\\config\\elasticsearch.yml				Intellect 4.10.3 and later	
<Intellect installation >\\Modules\\cam_title.run.config	ElasticSearchPort	0 - 65536	9200		The parameter sets the port <i>Intellect</i> sends data for Elastic Search search engine to. The value is to be the same as one specified in the elasticsearch.yml file (see above).
<Intellect installation >\\SlaveSettings.xml	DNS	-	-	-	This file stores the addresses of DNS servers specified using the <i>Advanced Setup</i> utility (see <a href="#">The Settings panel of the DNS section</a> ).
<Intellect installation >\\Modules\\cam_title.run.config	SearchIndex	True, False	True	up to Intellect 4.11.1	Enables the use of the Elastic Search search engine for titles search. True – Elastic Search is in use.
			False	Intellect 4.11.2 and later	False – Elastic Search is not in use.

## 2 Intellect Web Report System

XML file	Parameter	Available values	Default	Product version	Parameter in effect
<Directory of the Intellect software installation>\Modules\Wt2\Web.config	CamMonitorShift	-5000 - 5000	0		Sets shifting of video start while report viewing in milliseconds:  >0 – video will start later than time specified in a report  <0 – video will start earlier than time specified in a report
	FaceReplaceCameraIpFrom	IP-address	-	up to 3.2	Changes internal IP-address of a Server specified in the Architecture while viewing video for POS reports and for "Face" module report from outside
	FaceReplaceCameraIpTo	IP-address	-	up to 3.2	Changes external IP-address of a Server specified in the Architecture while viewing video for POS reports and for "Face" module report from outside
	WorkThroughGateway	true, false	false	from 3.3	Enables receiving video from Gateway while viewing video for POS reports and for "Face" module report. A Gateway is selected automatically.
	CommandTimeout	Time in seconds	200		Enables setting the timeout in seconds, during which waiting for data retrieval and report generation should occur.
	PersonNameLength	>=0	-	3.4	By default, the parameter is not added to the file (corresponds to value 1).  Add it to the <appSettings> section in the following format:  <add key = "PersonNameLength" value = "5" />  The parameter limits the user's patronymic to the number of characters specified in the value parameter for Access Manager and Time&Attendance reports. Example (if value = "5"): Ivanov Peter Alex.  If value = "0", the full name is displayed completely, without abbreviations. Example: Ivanov Peter Alexandrovich.

XML file	Parameter	Available values	Default	Product version	Parameter in effect
	PersonNameIncludesId	0, 1	-	3.4	<p>By default, the parameter is not added to the file (corresponds to value 0).</p> <p>Add it to the &lt;appSettings&gt; section in the following format:</p> <pre>&lt;add key = "PersonNameIncludesId" value = "1" /&gt;</pre> <p>The parameter allows enabling display of the user ID in parentheses after the user full name in the Access Manager and Time&amp;Attendance reports.</p> <p>value = "1" - the user ID in parentheses is displayed after the user full name. Example: Ivanov Peter Alexandrovich (1)</p> <p>value = "0" - the user ID is not displayed.</p>
	SweatheartingEnabled	0, 1	0	3.4	Enables the <b>Sweathearting</b> report.
	SweatheartingAddItemPosFunctionNumber	>=0	-	3.4	Sets the <b>Adding product to document</b> function number from the dbo.FuncDic table, which is necessary for the <b>Sweathearting</b> report proper operation.
	SweatheartingBeginReceiptPosFunctionNumber	>=0	-	3.4	Sets the function number used as the receipt beginning from the dbo.FuncDic table.
	SweatheartingEndReceiptPosFunctionNumber	>=0	-	3.4	Sets the function number used as the receipt ending from the dbo.FuncDic table.
	SweatheartingFilterByReceiptIntervals	0, 1	0	3.4	Enables the sweathearting events filtering so that only the events which occurred while the receipt was open were displayed in the <b>Sweathearting</b> report.
	SweatheartingAddTimeoutMs	>=0	500	3.4	Sets the timeout between the sweathearting detector event and the POS event. If this timeout is exceeded, the sweathearting event is added to the <b>Sweathearting</b> report.
	SweatheartingBeepEnabled	0, 1	0	3.4	Disables the sound notification about new events in the <b>Sweathearting</b> report.
	SweatheartingStepCount	>=0	1000	3.4	Sets the required number of the events which should be preloaded on the first <b>Sweathearting</b> report launch.

XML file	Parameter	Available values	Default	Product version	Parameter in effect
	SweatheartingPreloadDays	>=0	140	3.4	Sets the required number of days the events from which should be displayed on the first <b>Sweathearting</b> report launch.
	ExtendedPresenceReportInWorkplace	true, false	false	only 3.4	Enables an advanced display of the reports: <b>Presence at workplace report</b> and <b>Total report on the presence at the workplace</b> .
	EnablePasskindReport	true, false	false	3.4	Activates an <b>Issued pass cards report</b> .
	lpServerUrl	IP-address	http://localhost:10001/lprserver	3.4	Sets the server address where the recognized LP images and the vehicle frames are stored.
	IntellectVideoStreamNumber	0-4	0	3.4	Sets the required camera stream number in live video reports (0 is the first camera stream).
	ShowIconNewCashier	true, false	true	3.4	Highlights the new cashier's name in <b>POS</b> reports with the asterisk and the different color (the new cashiers are those who work less than a number of days specified in the CountDaysNewCashier key).
	CountDaysNewCashier	>=0	30	3.4	Sets the number of days within which the cashier is considered a new one (the key is used together with the ShowIconNewCashier key).
	QueueLengthDelta	0, 0.5	0.5	3.4	Sets the values threshold that are included into the table reports by Queue Length detectors:  0 - values equal to 0 and greater are included in the report.  0.5 - only the values greater than 0.5 are included in the report.
	GenderAnalyticsUrl	IP address	http://localhost:10000/firserver	3.5	Sets the address of the server where the Face Recognition Server is located (see <a href="#">Configuring the Gender analytics report</a> ).
	ReportSystemHost	IP address	localhost	3.5	Sets the address of the server on which the <i>Intellect</i> software package is located. It is necessary for the <b>Face recognition report</b> (see <a href="#">Face recognition report</a> ) and <b>Report by employee passes with</b>

XML file	Parameter	Available values	Default	Product version	Parameter in effect
					<b>photo</b> (see <a href="#">Report by employee passes with photo</a> ).
<Intellect installation directory>\Modules\Wt2\App_Data\Settings\DateFormat.config	ServerDateTimeFormat	Date and time format	d MMMMM yyyy HH:mm:ss	3.4	Sets the date and time format in General Reports (see <a href="#">Configuring the date and time format in General Reports</a> ).
<Intellect installation directory>\Modules\Wt2\App_Data\Mail\web.config	<configuration><system.net><mailSettings><smtp> from	String	-	-	Email address from which the auto-generated reports will be sent (see <a href="#">SMTP Server setup</a> ).
	<configuration><system.net><mailSettings><smtp> host	String	-	-	SMTP Server name (see <a href="#">SMTP Server setup</a> ).
	<configuration><system.net><mailSettings><smtp> password	String	-	-	Password of the account used for sending the messages to SMTP Server (see <a href="#">SMTP Server setup</a> ).
	<configuration><system.net><mailSettings><smtp> port	>=0	25	-	Port number used by SMTP Server (see <a href="#">SMTP Server setup</a> ).
	<configuration><system.net><mailSettings><smtp> userName	String	-	-	Name of account used for sending the messages to SMTP Server (see <a href="#">SMTP Server setup</a> ).
	<configuration><system.net><mailSettings><smtp> enableSsl	true, false	false	-	Enables the SSL encoding to connect to the SMTP Server (see <a href="#">SMTP Server setup</a> ).
<Intellect installation directory>\Modules\Wt2\App_Data\Settings\Settings.config	CurrencyFormat	String	₪	3.5	Sets the currency display format for the report by the number of goods with specific action.
	IsPersianLanguageUse	true, false	false	3.5	Enables the numbers filtering using the Persian alphabet and numbers.  <i>Note. If this key is set to true, then the IsArabicLanguageUse key should be set to false.</i>
	IsArabicLanguageUse	true, false	false	3.5	Enables the numbers filtering using the Arabic alphabet and numbers.  <i>Note. If this key is set to true, then the IsPersianLanguageUse key should be set to false.</i>

### 3 FACE-Intellect

XML file	Parameter	Available values	Default	Parameter in effect
<Directory of the Intellect software installation>\Modules\face_client.run.config	ProblemImages	Path to a folder	None	Specifies the path to the folder for storing images which have been skipped (there are 2 or more faces in the image, or the face was not recognized due to the poor image quality) during the automatic adding of faces from the folder (see <a href="#">Adding images to the reference face database</a> ). The specified folder will be created automatically.  <i>Note. If %USER% is specified in the parameter value, the images which haven't been added to the database will be stored in the folder: C:\Users\%LOGGED_USER%\AppData\Local\AxxonSoft\FaceIntellect\ProblemImages\</i>
	Timeout	>=0	60000	Specifies the waiting timeout for the face search results in milliseconds.
	Port	>=0	10000	Specifies the TCP port for face_client.run.
	RemoteUrl	IP addresses	none	Specifies the sending address of the HTTP POST request. It is used for the images transfer to an external system (see <a href="#">Configuring the images transfer to an external system</a> ).
	AnalycTimeout	>=0	100000	Specifies the time in milliseconds for refreshing the analytical data in the <b>Face recognition and search</b> interface object. When the time expires, the <b>Operation has timed out</b> error will be displayed (see <a href="#">Viewing the analytical data</a> ).
	PasserByFramePerCamera	>=0	10	Specifies the maximum number of comparison results for one camera. A value of <b>0</b> means that the number of comparisons is unlimited.
	HideViewButton	true, false	False	Hides the "View" button from the interface for monitoring of captured and recognized faces (see <a href="#">Monitoring of captured and recognized faces</a> ).
	SimpleMode	true, false	False	Enables the Simple mode of monitoring, which makes the upper part of the <b>Face recognition and search</b> interface window hidden, and such operations as working with the reference face database, face searching in the video archive, and some others unavailable (see <a href="#">Enabling the Simple mode of captured and recognized faces monitoring</a> ).
	AutoFollowTimeSeconds	>=0	120	Specifies the time in seconds after which the <b>Follow new faces</b> checkbox will be set automatically, if it is unset. The <b>0</b> value means that the checkbox will not be set automatically (see <a href="#">Monitoring of captured and recognized faces</a> ).
	CounterRowCount	>=0	0	Specifies the maximum number of rows (unique faces) in the generated report on analytical data (see <a href="#">Viewing the analytics</a> ). The <b>0</b> value means there is no limit.
HideCheckBoxIntellectPerson	true, false	False	Hides the <b>Create a user in the Intellect database</b> checkbox and assigns a unique <b>Person_ID</b> to each face when adding it to the reference face database (see <a href="#">Adding images to the reference face database</a> ).	
HideResultsWithoutImages	true, false	False	Hides the face search results with the face images damaged due to the emergency shutdown of the <i>FACE-Intellect</i> server.	
<Directory of the Intellect software installation>\Modules64\firserver_replicate.run.config	LogBadImages	true, false	False	Enables saving "bad" photos of faces when the <b>Face database replication</b> module is used (see <a href="#">Face database replication</a> ). Photos of faces which could not be added will be saved on the main Server in the folder <Directory of the Intellect software installation>\Modules64\Firserver_replicate_problem_images

## 4 Axxon Player

XML file	Parameter	Avai labl e valu es	Def aul t	Parameter in effect
<Intellect installation directory>\ Tools\Axxon_player.x ml	Most of the parameters are filled in automatically in the <i>Axxon Player</i> interface. Below are the options that are not available in the interface.			
	Render	0, 1	1	Sets the type of render: 0 - rendering is performed in OpenGL. 1 - rendering is performed in Direct3d.